

TRM240

INDUSTRIAL CELLULAR MODEM



TRM240 360° VIEW



Copyright © 2024, UAB TELTONIKA NETWORKS. Specifications and information given in this document are subject to change by UAB TELTONIKA NETWORKS without prior notice.



KEY FEATURES

HARDWARE

| Mobile | 4G/LTE (Cat 1), 3G, 2G |
|---------------------------|---|
| Powering option | microUSB, 5 VDC |
| SIM | 1 x Internal SIM holder (2FF) |
| Antenna connectors | 1 x SMA for mobile |
| USB | 1 x Micro USB slave |
| Status LEDs | 1 x LTE, 1 x Network, 1 x Power |
| Ingress protection rating | IP30 |
| Operating humidity | 10 % to 90 % non-condensing |
| Operating temperature | -40 °C to 75 °C |
| Housing | Aluminium housing with DIN rail mounting option |
| Dimensions (W x H x D) | 74.5 x 25 x 64.5 mm |
| Weight | 131 g |

SOFTWARE

| Network manager | Windows 7/8/8.1/10 Linux distributions |
|-------------------------|---|
| USB serial driver | Windows 7/8/8.1/10 Windows CE 5.0/6.0 Linux 2.6~5.4 Android 4.x/5.x/6.x/7.x/8.x |
| RIL driver | Android 4.x/5.x/6.x/7.x/8.x |
| NDIS driver | Windows 7/8/8.1/10 |
| Gobinet driver | Linux 2.6~5.4 |
| QMI_WWAN driver | Linux 3.4~5.4 |
| Control via AT commands | 3GPP TS27.007 and enhanced AT commands |



